

Stockmaster™ TRACKER

What's so special about a Stockmaster Tracker Mobile Platform?

It gets the job done quicker, here's why:

- It moves easily over unsealed surfaces and slopes
 - It is fast to move around and needs no setting up
 - It has a safety railing system that adjusts to suit the job
 - It is available with an automatic gate at the platform entry
 - It meets Australian, New Zealand and European Standards
- and there's a size to suit your job.**

Stockmaster Tracker is a very versatile and easy to use mobile work platform. With two large diameter wheels it moves easily over sealed or unsealed surfaces and slopes making it ideal for both indoor and outdoor use. Featuring a Tilt, Steer and Brake control it is fast and easy to move around. Taking hold of the control raises the unit to the mobile position to move to the job. *Release of the control automatically returns it to the stationary mode where it is braked and totally stable.*

One control does it all creating a much safer product.

With the Tilt, Steer and Brake control actuated, the operator is positioned away from the front of the ladder to allow a normal walking step, and the unit moves easily to the job with minimal effort. Tracker moves to the job in much less time than competing products and requires no set up when you get there. *Tracker is easier and faster to move around and saves time on the job.*

*Tracker is supplied with a flexible Platform Safety Rail system which can be set up to three different configurations to provide improved ergonomics and easy access for the job; maintenance tasks, process inspection, and many other applications, and when fitted with the **Auto-Safe Gate** the operator is protected from accidentally stepping off the front of the platform.*

Stockmaster Tracker is a modular design enabling parts replacement in the event of accidental damage. It is manufactured from high quality materials and built to last. With reasonable care Stockmaster Tracker will give many years of service, *and get the job done.*

Stockmaster Tracker, in every way a **SAFE CHOICE!**



Stockmaster™
A SAFE CHOICE

Stockmaster Tracker Size Selection Chart

Tracker Size code	SM-T03	SM-T04	SM-T05	SM-T06	SM-T07	SM-T08	SM-T09	SM-T10	SM-T11	SM-T12	SM-T13	SM-T14
Platform Height millimeters	860	1145	1435	1720	2005	2295	2580	2865	3155	3440	3735	4015
Working Range Meters	1.4 - 2.8	1.7 - 3.1	2.0 - 3.4	2.3 - 3.7	2.5 - 3.9	2.8 - 4.2	3.1 - 4.5	3.4 - 4.8	3.7 - 5.1	4.0 - 5.4	4.3 - 5.7	4.6 - 6.0
It is unsafe to handle large or heavy items (above 5kg) in working ranges above 2.6 meter without a lifting aid. See Stockmaster WinchTruk												

This selection chart must be used only as a guide for the Working Range.
The Working Range is the height above ground at which an operator can work when standing on the platform.
The Operating Environment must also be known before a final choice of the product is made.

Stockmaster Patents are issued and pending in Australia, New Zealand, Europe and North America